



3281 Guasti Road, Suite 260 Ontario, CA 91761

(909) 987-0550 (800) 538-3091 Fax: (909) 987-0490

http://www.supergluecorp.com

PRODUCT SALES SHEET: Zip Kicker

Pacer Technology Hobby Zip Kicker (PT-715, PT-29) and Zip Kicker Aerosol (PT-15, PT-50) are solvent-based accelerators to be used with Super Glues and all of the Zap line quick set adhesives. The Zip Kicker formula will force the immediate cure of all cyanoacrylates, but will not craze most plastic surfaces. Zip Kicker expands the gap filling ability of the adhesives, permits structural fillet forming and solves most tough-to-bond combinations of surface materials.

PROPERTIES: Appearance: Thin, straw-colored liquid with solvent odor.

USE INSTRUCTIONS: (**NOTE** – Not for use in cosmetic applications. Not recommended for granite or other natural stone materials).

- 1. Use in a well-ventilated area with fresh air source.
- 2. Product can be applied to surfaces prior to application of adhesive to set adhesive surface. Zip Kicker can also be applied to outside edge of bond to secure parts immediately.
- 3. Using Zip Kicker can influence the overall strength of adhesive bonds.

STORAGE AND SHELF LIFE:

Store in cool area away from sunlight or heat. Stored under these conditions, a one-year shelf life can be expected.

SAFETY AND HANDLING PRECAUTIONS:

DANGER: VAPOR HARMFUL. HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE. Contains petroleum distillates & aromatic amine. Use & store in well-ventilated area away from heat or flame. Avoid prolonged breathing of vapor. If swallowed, do not induce vomiting. Call physician immediately and show container label. Contains a bittering agent to discourage ingestion. **KEEP OUT OF REACH OF CHILDREN.**

WARNING: This product contains a chemical known to the state of California to cause cancer and birth defects or other reproductive harm.

<u>PT-15, PT-50 Aerosol</u>: Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

For more information, refer to Material Safety Data Sheet available upon request or obtain from our Pacer Technology website @ www.supergluecorp.com and click on the ZAP logo. In case of emergency, call CHEMTREC at (800) 424-9300 or call Pacer Technology (800) 538-3091 (outside CA only) or (909) 987-0550.

Rev 3 - 2016 kr

The information in this Product Data Sheet (PDS) is of a general nature based on our knowledge and experience with this product and should be used for information and consideration purposes only. The product can have a variety of different applications, as well as differing application and working conditions in your environment that are beyond our control. Therefore, this data does not constitute a warranty, expressed or implied, statutory or otherwise, nor is it representation for which Pacer Technology assumes legal responsibility. Pacer Technology strongly recommends that users of the product independently determine the suitability of the product for their use.

Pacer Technology specifically disclaims any liability for consequential or incidental damages of any kind, including profit. Any use of this product must be determined by the user to be in accordance with applicable federal, state, provincial, and local laws and regulations.